

FORM PTO-1390
REV. 5-93U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICEATTORNEYS DOCKET NUMBER
P99,2691**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)

09/446752

INTERNATIONAL APPLICATION NO.

PCT/DE97/01731

INTERNATIONAL FILING DATE

December 30, 1998

PRIORITY DATE CLAIMED

June 24, 1997TITLE OF INVENTION **RADIO INTERFACE FOR A CORDLESS EMAIL SYSTEM USING THE 2.4 GHZ ISM BAND**

APPLICANT(S) FOR DO/EO/US

JUERGEN KOCKMANN, UWE SYDON and HERMANN-JOSEF TERGLANE

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:


1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay.
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of International Application
 - a. ☐ is transmitted herewith
 - b. ☒ has been transmitted by
 - c. ☐ is not required, as the a
6. ☒ A translation of the International
7. ☐ Amendments to the claims of the
 - a. ☐ are transmitted herewith
 - b. ☐ have been transmitted
 - c. ☐ have not been made; h
 - d. ☐ have not been made at
8. ☐ A translation of the amendments
English translation of application
9. ☐ An oath or declaration of the inventor
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

*PCT Number are different
Please check the
use this one
DE97/01731*

Items 11. to 16. below concern other document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 C.F.R. 1.97 and 1.98; (PTO 1449, Prior Art, Search Report).
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 C.F.R. 3.28 and 3.31 is included.
(SEE ATTACHED ENVELOPE)
13. ☐ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:
 - a. ☒ Submission of Drawings
 - b. ☐ Request for Approval of Drawing Changes
 - c. ☐ Letter Under Rule Under 37 C.F.R. §1.41(c)
 - d. ☒ EXPRESS MAIL #EL408260753US

09:46:52.053000

U.S. APPLICATION NO (if known, see 37 C.F.R. 1.5) 09/446752		INTERNATIONAL APPLICATION NO PCT/DE97/01731		ATTORNEY'S DOCKET NUMBER P99,2691	
17. <input checked="" type="checkbox"/> The following fees are submitted:				CALCULATIONS	
BASIC NATIONAL FEE (37 C.F.R. 1.492(a)(1)-(5): Search Report has been prepared by the EPO or JPO \$840.00 International preliminary examination fee paid to USPTO (37 C.F.R. 1.482) ... \$760.00 No international preliminary examination fee paid to USPTO (37 C.F.R. 1.482) but international search fee paid to USPTO (37 C.F.R. 1.445(a)(2)) \$450.00 Neither international preliminary examination fee (37 C.F.R. 1.482) nor international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO \$1,250.00 International preliminary examination fee paid to USPTO (37 C.F.R. 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) \$98.00				PTO USE ONLY	
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$ 840.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(e)).				\$	
Claims	Number Filed	Number Extra	Rate		
Total Claims	14 - 20 =		X \$ 18.00	\$ 0.00	
Independent Claims	2 - 3 =		X \$ 78.00	\$ 0.00	
Multiple Dependent Claims			\$270.00 +	\$ 270.00	
TOTAL OF ABOVE CALCULATIONS =				\$1,110.00	
Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity statement must also be filed. (Note 37 C.F.R. 1.9, 1.27, 1.28)				\$	
SUBTOTAL =				\$1,110.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
TOTAL NATIONAL FEE =				\$	
Fee for recording the enclosed assignment (37 C.F.R. 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 C.F.R. 3.28, 3.31). \$40.00 per property				SEE ATTACHED ENVELOPE	
TOTAL FEES ENCLOSED =				\$1,110.00	
				Amount to be refunded	\$
				charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$ 1,110.00 to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 08-2290 . A duplicate copy of this sheet is enclosed. NOTE: Where an appropriate time limit under 37 C.F.R. 1.494 or 1.495 has not been met, a petition to revive (37 C.F.R. 1.137(a) or (b)) must be filed and granted to restore the application to pending status.					
SEND ALL CORRESPONDENCE TO:					
Hill, Steadman & Simpson A Professional Corporation 85th Floor Sears Tower Chicago, Illinois 60606					
Signature  NAME 28,982 Registration Number					

2/PRTS

09/446752

430 Rec'd PCT/PTO 2 2 DEC 1999

GR 97 P 2123 P

Description

Radio interface for a cordless small system using the 2.4 GHz ISM band

5 The present invention relates to a method and a transmission system according to the precharacterizing clause of the independent claims. According to the invention, a radio interface is provided for a cordless small system using the 2.4 GHz ISM band.

10 The DECT Standard was adopted at the start of the 1990's in order to replace the various existing analogue and digital Standards in Europe. This is the first common European Standard for cordless telecommunications. A DECT network is a microcellular, digital mobile radio network for high subscriber densities. It is primarily designed
15 for use in buildings. However, it is also possible to use the DECT Standard outdoors. The capacity of the DECT network of around 10,000 subscribers per square kilometer provides, from the cordless standard, ideal access technology for network operators. According to the DECT
20 Standard, it is possible to transmit both voice and data signals. Thus, cordless data networks can also be built on a DECT base.

25 The DECT Standard will be explained in more detail in the following text with reference to Fig. 2. A digital, cordless telecommunications system has been standardized for Europe under the designation DECT (Digital Enhanced Cordless Telecommunication). In conjunction with the switching function of a telecommunications installation, this system is therefore
30 suitable for mobile telephone and data traffic in an office building or on a commercial site. The DECT functions supplement a telecommunications installation, and thus make it the fixed station FS of the cordless telecommunications system. Digital radio links between the
35 fixed station FS and a maximum of 120 mobile stations MS can be produced, monitored and controlled on up to 120 channels.

09/446752-000000

A maximum of ten different carrier frequencies (carriers) are used for transmission in the frequency range from 1.88 GHz to 1.9 GHz. This frequency-division multiplex method is called FDMA (Frequency Division
5 Multiple Access).

Twelve channels are transmitted successively in time on each of the ten carrier frequencies using the time-division multiplex method TDMA (Time Division Multiple Access). Cordless telecommunication in accordance with the DECT Standard using ten carrier frequencies with in each case twelve channels provides a total of 120
10 channels. Since one channel is required, for example, for each voice link, there are 120 links to the maximum of 120 mobile stations MS. The duplex method (TTD) is used
15 on the carriers. Once the twelve channels (channels 1 - 12) have been transmitted from the fixed station, it switches to receive and receives twelve channels (channels 13 - 24) in the opposite direction from at least one mobile station.

20 A time-division multiplex frame thus comprises 24 channels (see Fig. 2). In this case, channel 1 to channel 12 are transmitted from the fixed station FS to the mobile stations MS, while channel 13 to channel 24 are transmitted in the opposite direction, from the mobile
25 stations MS to the fixed station FS. The frame duration is 10 ms. The duration of a channel (time slot) is 417 μ s. 320 bits of information (for example voice) and 104 bits of control data (synchronization, signalling and error check) are transmitted in this time. The useful bit
30 rate for a subscriber (channel) results from the 320 bits of information within 10 ms. It is thus 32 kilobits per second.

Integrated modules have been developed to carry out the DECT functions for fixed and mobile stations. In
35 this case, the fixed station and the mobile station carry out similar functions. One of these said integrated modules is in this case the RF module, that is to say the module which carries out the actual function of receiving and transmitting in the RF band.

It is known for so-called fast hopping RF modules to be used, that is to say RF modules which can carry out a change in the carrier frequency from one time slot or channel to the next. These fast hopping RF modules are intrinsically very complex and costly. Thus, in practice, so-called slow hopping RF modules are mainly used, that is to say modules which require a certain amount of time to change the carrier frequency. In practice, the time period which the slow hopping RF module requires to change the carrier frequency corresponds essentially to the time period of a time slot. This means that, after each active time slot, that is to say after each slot in which data are transmitted, a so-called inactive time slot (blind slot) must follow, in which no data can be transmitted. This means that, in practice, only six links are available on one carrier frequency to the DECT Standard, instead of the twelve possible links.

A DECT channel is defined by its time slot and its carrier frequency. In this case, it should be noted that, according to the DECT Standard, the organization to re-use physical channels is carried out by means of dynamic channel selection. This means that there is no need for any complex frequency planning, as in cellular systems. To set up a link, the signal levels of all the channels are measured continuously, and the interference-free channels are controlled in a channel list (channel map). While a link exists, the signal levels of all the channels and the reception quality continue to be monitored. If this monitoring indicates that the channel currently being used has been transmitted at a carrier frequency which is subject to interference (for example as a result of the influence of a transmission at the same carrier frequency from or to another fixed station), another carrier frequency is automatically selected for the next active time slot, and is entered in the channel list as being interference-free.

As an alternative, a so-called frequency hopping method can also be used, in which the carrier frequency is changed after a predetermined time period, for example

0946752.053000

a transmission frame.

For nations outside Europe, the DECT Standard may need to be modified and matched to local conditions. For example, in the USA, the normal DECT band between 1.88 and 1.90 GHz cannot be used for transmission, and the generally accessible 2.4 GHz ISM band (Industrial, Scientific, Medical) is available instead of this. Furthermore, changes would have to be carried out for matching to the national Standards, such as the American Standard "FCC part 15" (Federal Communications Commission). This American Standard describes the transmission method, transmission powers and available bandwidth allowed for the radio interface.

In the DECT Standard, in addition to the 320 information bits mentioned above, each time slot also contains another 104 bits required for signal transmission, as well as 56 bits in the guard field, so that each time slot contains a total of 480 bits. This results in a data rate of $(24 \times 48 \text{ bits}) / 10 \text{ ms} = 1152000 \text{ bits/s}$. A data rate at this level is pointless in the American ISM band, since the bandwidth required per usable channel would be too large. Despite these Standards, for cost reasons, it should be possible to continue to use components developed for the DECT Standard, such as the base band controller, with as little modification as possible.

The present invention thus has the object of providing a radio interface for a cordless small system using the 2.4 GHz ISM band, which allows components which were developed for the so-called DECT Standard to be used as far as possible.

The object is achieved by the features in the independent claims.

Thus, according to the invention, a method for wire-free transmission of data is provided, the data being transmitted in time slots using a frequency-division multiplex method, a time-division multiplex method and with time division duplexing (TDD). As is known from the DECT Standard, the data are modulated onto the respective carrier frequency in accordance with the

GMSK modulation method. According to the invention, the carrier frequency is changed after a predetermined time period, this being called frequency hopping spread spectrum. According to the invention, a transmission
5 frame still has 16 time slots.

Between 80 and 100 carrier frequencies can advantageously be used.

The data can be transmitted in a frequency band between 2.4 and 2.483 GHz, as is the case, for example,
10 with the ISM band.

The predetermined time period after which the carrier frequency is changed in accordance with the frequency hopping spread spectrum method may correspond to a time slot or a transmission frame. The time period
15 may also be an integer multiple of a time slot or of a time frame.

An active time slot in which data are transmitted can in each case be followed by an inactive time slot, in which no data are transmitted. The time duration of the
20 inactive time slot may be half the time duration of the active time slots.

The setting (programming) of the carrier frequency for the respective next active time slot can be carried out during the inactive time slots.

According to the invention, a transmission system
25 for wire-free transmission of data is also provided, the transmission system having a transmitter and a receiver. The transmitter and the receiver in turn each have devices for transmitting data in time slots using a
30 frequency-division multiplex method (FDMA), a time-division multiplex method (TDMA) and with time division duplexing (TDD). The data are in this case modulated onto the carrier frequency, and demodulated, in accordance with a GMSK modulation method. According to the inven-
35 tion, the transmitter and the receiver are designed such that the carrier frequency is changed after a predetermined time period. One transmission frame contains 16 time slots.

Between 80 and 100 carrier frequencies can

advantageously be provided.

A frequency band between 2.4 and 2.4835 GHz can be provided for transmitting the data. The predetermined time period after which the carrier frequency is changed
5 can be set to the time duration of a time slot or, alternatively, of a transmission frame. The time period may also be an integer multiple of a time slot or of a time frame.

After an active time slot in which data are transmitted, an inactive time slot can in each case be provided, in which no data are transmitted.

The time duration of the inactive time slots may be chosen to be half the time duration of the active time slots.

15 An RF module can be provided in each case in the transmitter and the receiver, it being possible to select the carrier frequency of an active time slot of the RF module in each case during the preceding inactive time slot.

20 The invention will now be explained in more detail using an exemplary embodiment and with reference to the accompanying drawings, in which:

Fig. 1 shows an arrangement according to the invention for digital radio transmission of data,

25 Fig. 2 shows a schematic illustration of the known DECT Standard,

Fig. 3 shows a schematic illustration of the channel allocation for matching the known DECT Standard to the American ISM band,

30 Fig. 4 shows a particularly effective allocation of the channels from the DECT Standard matched to the ISM band, according to the invention.

Fig. 1 shows an arrangement for digital radio transmission of data. A fixed station 1 is in this case
35 connected to the fixed network by means of a terminal line 10. The fixed station 1 has an RF module 4, using which data can be transmitted and received by means of an antenna 6. The RF module 4 may be, in particular, a so-

called slow hopping RF module, that is to say a particularly cost-effective RF module, which intrinsically requires a certain period of time to change from one carrier frequency to another carrier frequency. This time period is in the order of magnitude of a time slot, that is to say between about 100 μ s and 1 ms, and, in particular, between about 300 μ s and 500 μ s. This time period required for the carrier frequency change may correspond, for example, to the time period which is filled by a time slot in a time-division multiplex method (TDMA). By means of the antenna 6, a radio transmission may be made via a radio transmission path 8 to a mobile station 2, or a radio transmission may be made to a mobile station (cordless telephone) 3 via a second radio transmission path 9. All the mobile stations illustrated in Fig. 1 are of the same design, so that a more detailed explanation will be given only on the basis of the illustrated mobile station 2.

As can be seen in Fig. 1, this mobile station 2 has an antenna 7 for receiving and for transmitting data from and, respectively, to the fixed station 1. The mobile station 2 contains an RF module 5, which essentially corresponds to the RF module 4 used in the fixed station 1. The RF module 5 of the mobile station 2 may thus also be a so-called slow hopping RF module.

It is now intended to explain, with reference to Fig. 2, how the known DECT Standard can be matched to the American ISM band. As already mentioned above, if the DECT Standard were retained, the resulting data rate would be too high for the ISM band. As can be seen in Fig. 3, the number of time slots per frame is for this reason halved, that is to say only 12 time slots Z1 - Z12 are now provided in the ten milliseconds of a time frame instead of the 24 time slots (channels) in the DECT Standard, each of which 12 time slots can be used to transmit 480 bits. By halving the number of time slots, the data rate is also halved, in a corresponding manner, to $(12 \times 480 \text{ bits})/10 \text{ ms} = 576000 \text{ bits/s}$. This lower data rate results in a bandwidth that is acceptable for the

American ISM band.

As can be seen, per se, in Fig. 3, it is necessary to provide so-called slow hopping RF modules in a cost-effective implementation of the equipment required for radio transmission, which means that each active time slot in which data are transmitted must be followed by an inactive time slot (blind slot), in which no data can be transmitted. If twelve time slots Z1 - Z12 are provided (6 time slots Z1 - Z6 for transmission from a fixed station to the mobile station and 6 time slots Z7 - Z12 for transmission from the mobile station to a fixed station), then there is a maximum of only three possible links available. In an implementation using the cost-effective slow hopping RF modules, the usable channel capacity is thus not very great as a result of the regulation by the slow hopping RF module to a maximum of three links.

Possible active time slots are illustrated shaded in Fig. 3. For example, as illustrated, transmission from the fixed station 1 to a mobile station 2, 3 can be made at the carrier frequency f_2 in the time slot Z1 (RX1). If this time slot Z1 is followed by a time slot Z2, in which no data transmission takes place (inactive time slot, blind slot), a slow hopping RF module can also use the time duration of the inactive time slot Z2 to change the carrier frequency. As illustrated in Fig. 3, the carrier frequency can be changed, for example, from the carrier frequency f_2 to the carrier frequency f_1 . Thus, as illustrated in Fig. 3, a transmission can be made in the time slot Z3 from the fixed station to a mobile station, at the carrier frequency f_1 (RX2). The layout shown in Fig. 3 is thus distinguished by the fact that, with a given time slot distribution, an active time slot (illustrated shaded) can be operated at each of the predetermined carrier frequencies ($f_1, f_2 \dots$).

It should be remembered that, according to the DECT Standard, the organization of re-use of physical channels is carried out by means of dynamic channel selection, a channel being defined by its carrier

frequency and its time slot. There is thus no need for any complex frequency planning, as in cellular systems. To set up links, the signal levels of all the channels are measured continuously, and the interference-free
5 channels are controlled in a channel list (channel map). During a link, the signal levels of all the channels of all the possible carrier frequencies, and the reception quality, continue to be monitored.

Thus, as illustrated in Fig. 3, if it is found in
10 the time slot Z1 when transmitting (RX1) at the carrier frequency f_2 that the reception or transmission conditions are better at the carrier frequency f_1 , then it is possible to change, during the time duration of the time slot Z2 in which no data transmission is taking place, to
15 the carrier frequency f_1 which has been identified as being better. The transmission RX2 takes place during the time slot Z3 at the carrier frequency f_2 which has been found to be better.

As a preferred alternative to this approach, in
20 which a carrier frequency is changed only in the event of a disturbance, a so-called frequency hopping method (frequency hopping spread spectrum) can also be used, in which the carrier frequency is changed after a pre-determined time period, for example a transmission frame
25 or a transmission time slot, irrespective of whether the currently used carrier frequency is or is not subject to interference. The transmitted energy can thus be distributed over a plurality of carrier frequencies which, overall, leads to less adverse effect on other systems
30 within the transmitter range.

Care must be taken in this case to ensure that all the carrier frequencies are, on average, used equally often, in accordance with the Standard "FCC part 15".

As already stated, the channel allocation scheme
35 illustrated in Fig. 3 has the disadvantage that, since the number of time slots per time frame is halved to 12, as a result of which the duration of a time slot is doubled to 833 μs , and as a result of the necessity for the inactive time slots after each active time slot, this

results in only three possible links (three links from a fixed station to a mobile station and three links from a mobile station to a fixed station) being available, in contrast to the six possible links according to the DECT Standard.

Fig. 4 illustrates a time slot structure which allows the maximum possible number of links to be increased from three to four without there being any negative effect on flexible selection of the carrier frequencies from one active time slot to the next active time slot and without the programming of the synthesizers of the RF modules 4, 5 being adversely effected. As can be seen in Fig. 4, this increase in the maximum number of links from three to four is essentially achieved by the time duration of an inactive slot, during which no data transmission takes place, being shortened in comparison with the time duration of an active time slot. As is shown in Fig. 4, the time duration of an active time slot Z1, Z3, Z5, Z7, Z9, Z11, Z13 and Z15 in a time frame is in each case 833 μ s, if the time frame lasts for 10 ms overall. The time duration of the inactive time slots Z2, Z4, Z6, Z8, Z10, Z12, Z14 and Z16 is only 417 μ s, as illustrated in Fig. 4, and is thus essentially only half the time duration of the active time slots. A slow hopping RF module known from DECT technology requires a time period of at least 417 μ s after an active time slot, in order to carry out frequency programming for the carrier frequency of the next time slot. Half a time slot of the DECT Standard matched to the ISM band, with a time duration of $833 \mu\text{s}/2 = 417 \mu\text{s}$, is thus sufficient for an inactive time slot (blind slot).

As can be seen in Fig. 4, a data transmission RX1, for example, can be made during the time slot Z1 from the fixed station to a mobile station at a carrier frequency f_1 . In order to allow the transmission to be made with a low bandwidth as well, the time duration of the time slot Z1 is in this case twice the time duration according to the DECT Standard, namely 833 μ s. The time slot Z1 is followed by a non-active time slot Z2, whose

time duration is only 417 μ s. This time period of 417 μ s is intrinsically sufficient for an RF module using the slow hopping technique to program the carrier frequency for the next active time slot Z3. If it is thus found
5 that, for example, the carrier frequency f_3 offers better reception conditions than the carrier frequency f_1 , the carrier frequency [lacuna] from the carrier frequency f_1 in time slot Z1 to the carrier frequency f_3 for the time slot Z3 can take place during the time duration of the
10 time slot Z2 during which no data transmission takes place, and a transmission from a fixed station to a mobile station can thus take place during the time slot Z3 (RX3).

The illustrated example shows the case where the
15 carrier frequency f_x is not changed for transmission between a fixed station and a specific mobile station.

As an alternative, of course, a so-called frequency hopping method can also be used, in which the carrier frequency is changed after a predetermined time
20 period, for example a transmission frame.

After eight time slots Z1 to Z8, which correspond to half the time slots Z1 to Z16 in a time frame of 10 ms, the mobile station or stations transmit to the fixed station using the duplex method (TTD). For example,
25 a mobile station can transmit (TX1) to the fixed station at a carrier frequency f_1 during the time slot Z9. The inactive time slot Z10 following the active time slot Z9 once again lasts for only half the time duration of the active time slot Z9 (833 μ s), namely 417 μ s. The time
30 duration of the inactive half time slot Z10 is in turn sufficient for the RF module to carry out the frequency programming for the next active time slot Z11, for a further transmission from a mobile station to the fixed station (TX2).

35 The following table shows details of the parameters of the radio interface according to the invention, as they have been determined as being particularly

0946752.053000

advantageous:

5	Frequency band	2.4 - 2.4835 GHz ISM band
	Transmission method	Frequency Hopping Spread Spectrum
	Access method	FDMA/TDMA
	Duplex method	TDD
	Number of carrier frequencies	96
10	Carrier frequency separation	0.864 MHz
	Carrier frequencies (MHz)	$f_n = 2401.056 + n \times 0.864$, where $n = 0 \dots 95$
	Number of carrier frequencies	96
	Maximum number of channels	384
	Number of channels which can be allocated simultaneously	4
15	Transmitted power (peak)	250 mW (up to 1 watt possible)
	Range	as DECT (≈ 300 m)
	Modulation method	GMSK ($B \times T = 0.5$)
	Frame length	10 ms (5 ms Rx, 5 ms Tx)
	Number of time slots per Uplink/Downlink	4 full slots (active time slots) 4 half slots (inactive time slots for setting the synthesizers in the RF modules)
20	Bit rate	576 kbits/s

According to the invention, a radio interface is thus provided in particular for the 2.4 GHz band which, taking account of the Standards applicable to this band (FCC part 15), is based on the DECT Standard such that it can be implemented, for example, with the aid of only insignificantly modified DECT base band controllers and RF modules.

List of reference symbols

- 1: Fixed station
- 2: Mobile station (cordless telephone)
- 3: Mobile station
- 5 4: RF module, fixed station
- 5: RF module, mobile station
- 6: Antenna, fixed station
- 7: Antenna, mobile station
- 8: First radio transmission path
- 10 9: Second radio transmission path
- 10: Terminal line
- Zx: Time slots
- f_x : Carrier frequency

Patent Claims

1. Method for wire-free transmission of data, the data being transmitted in time slots (Z_x) using a
- frequency-division multiplex method (FDMA),
 - 5 - time-division multiplex method (TDMA) and with
 - time division duplexing (TDD), and
 - the data being modulated onto a carrier frequency (f_x) using a GMSK modulation method, characterized in that
- 10 - the carrier frequency (f_x) is changed after a pre-determined time period, and
- a transmission frame contains 16 time slots (Z_x).
2. Method according to one of the preceding claims, characterized in that
- 15 - between 80 and 100 carrier frequencies (f_x) are used.
3. Method according to one of the preceding claims, characterized in that the data are transmitted in a frequency band between 2.4 and 2.4835 GHz.
- 20 4. Method according to one of the preceding claims, characterized in that the predetermined time period after which the carrier frequency (f_x) is changed corresponds to a time slot, a transmission frame or an integer multiple of a time slot
- 25 or of a frame.
5. Method according to one of the preceding claims, characterized in that an active time slot in which data are transmitted is in each case followed by an inactive time slot, in which no
- 30 data are transmitted.
6. Method according to Claim 5, characterized in that the time duration of the inactive time slots is half the time duration of the active time slots.
- 35 7. Method according to one of Claims 5 or 6, characterized in that the carrier frequency (f_x) for the next active time slot is set during the inactive time slot.

00440752-00000000

8. Transmission system for wire-free transmission of data, having a fixed station (1) and at least one mobile station (2, 3),
the fixed station (1) and the mobile station (2) each
5 having devices (4, 5) in order to transmit the data in time slots using a
- frequency-division multiplex method (FDMA),
 - time-division multiplex method (TDMA) and with
 - time division duplexing (TDD), and
- 10 - to modulate the data onto a carrier frequency (f_x), and to demodulate them, using a GMSK modulation method,
- characterized in that
the devices (4, 5) in the fixed station (1) and the
15 mobile station (2) are designed such that the carrier frequency (f_x) is changed after a predetermined time period, and in that a transmission frame contains 16 time slots.
9. Transmission system according to Claim 8,
20 characterized in that
between 80 and 100 carrier frequencies (f_x) are provided.
10. Transmission system according to one of Claims 8 or 9,
characterized in that
25 a frequency band of between 2.4 and 2.4835 GHz is provided for transmission of the data.
11. Transmission system according to one of Claims 8 to 10,
characterized in that
30 the predetermined time period after which the carrier frequency (f_x) is changed is set to the time duration of a time slot, of a transmission frame or of an integer multiple of a time slot or of a frame.
12. Transmission system according to one of Claims 8
35 to 11,
characterized in that
an active time slot in which data are transmitted is in each case followed by an inactive time slot, in which no data are transmitted.

13. Transmission system according to Claim 12, characterized in that the time duration of the inactive time slots is half the time duration of the active time slots.

- 5 14. Transmission system according to one of Claims 12 or 13,

characterized in that

- an RF module (4, 5) is provided in each case in the fixed station (1) and in the mobile station (2, 3), it being possible to select the carrier frequency (f_x) of an active time slot in the RF module in each case during the preceding inactive time slot.
- 10

000000-2570460

Abstract

Radio interface for a cordless small system using the 2.4 GHz ISM band

The present invention relates to a radio interface for a cordless small system using the 2.4 GHz ISM band. According to the present invention, a transmission system having a fixed station (1) and at least one mobile station (2, 3) is provided for this purpose, the fixed station (1) and the mobile station (2) each having devices (RF modules 4, 5) in order to transmit the data in time slots using a frequency-division multiplex method (FDMA) and a time-division multiplex method (TDMA), and with time division duplexing (TDD). As is known from DECT Standard, the data are modulated onto a carrier frequency (f_x) using a GMSK modulation method. The RF modules (4, 5) in the fixed station (1) and, respectively, the mobile station (2) are in this case designed such that the carrier frequency (f_x) is changed after a predetermined time period, which may correspond, for example, to the time duration of a time slot or of a transmission frame. A transmission frame in this case contains 16 time slots.

Figure 1

1/2

FIG 1





FIG 2



2/2

Carrier frequency f_x

FIG 3



Carrier frequency f_x

FIG 4





DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION
ERKLÄRUNG FÜR PATENTANMELDUNGEN MIT VOLLMACHT
German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit
an Eides Statt:

dass mein Wohnsitz, meine Postanschrift, und meine
Staatsangehörigkeit den im Nachstehenden nach
meinem Namen aufgeführten Angaben entsprechen,

dass ich, nach bestem Wissen der ursprüngliche, erste
und alleinige Erfinder (falls nachstehend nur ein Name
angegeben ist) oder ein ursprünglicher, erster und
Miterfinder (falls nachstehend mehrere Namen
aufgeführt sind) des Gegenstandes bin, für des dieser
Antrag gestellt wird und für den ein Patent beantragt
wird für die Erfindung mit dem Titel:

deren Beschreibung

(zutreffendes ankreuzen)

☐ hier beigefügt ist.

☒ am 14.8.97 als
PCT internationale Anmeldung
PCT Anwendungsnummer PCT/DE97/01731
eingereicht wurde und am _____
abgeändert wurde (falls tatsächlich abgeändert).

Ich bestätige hiermit, dass ich den Inhalt der obigen
Patentanmeldung einschliesslich der Ansprüche
durchgesehen und verstanden habe, die eventuell durch
einen Zusatzantrag wie oben erwähnt abgeändert
wurde.

Ich erkenne meine Pflicht zur Offenbarung
irgendwelcher Informationen, die für die Prüfung der
vorliegenden Anmeldung in Einklang mit Absatz 37,
Bundesgesetzbuch, Paragraph 1.56(a) von Wichtigkeit
sind, an.

Ich beanspruche hiermit ausländische Prioritätsvorteile
gemäss Abschnitt 35 der Zivilprozessordnung der
Verinigten Staaten, Paragraph 119 aller unten
angegebenen Auslandsanmeldungen für ein Patent oder
eine Erfindersurkunde, und habe auch alle
Auslandsanmeldungen für ein Patent oder eine
Erfindersurkunde nachstehend gekennzeichnet, die ein
Anmeldedatum haben, das vor dem Anmeldedatum der
Anmeldung liegt, für die Priorität beansprucht wird.

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as
stated below next to my name,

I believe I am the original, first and sole inventor (if only
one name is listed below) or an original, first and joint
inventor (if plural names are listed below) of the subject
matter which is claimed and for which a patent is sought
on the invention entitled

RADIO INTERFACE FOR A CORDLESS EMAIL
SYSTEM USING THE 2.4 GHZ ISM BAND

the specification of which

(check one)

☐ is attached hereto

☒ was filed on August 14, 1997 as
PCT international application
PCT Application No. PCT/DE97/01731
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the
contents of the above identified specification, including
the claims as amended by any amendment referred to
above.

I acknowledge the duty to disclose information which is
material to the examination of this application in
accordance with Title 37, Code of Federal Regulations,
§1.56(a).

I hereby claim foreign priority benefits under Title 35,
United States Code, §119 of any foreign application(s)
for patent or inventor's certificate listed below and have
also identified below any foreign application for patent or
inventor's certificate having a filing date before that of
the application on which priority is claimed:

German Language Declaration

Prior foreign applications

Priorität beansprucht

Priority Claimed

PCT/DE97/01315 World
(Number) (Country)
(Nummer) (Land)
June 24, 1997
(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☒ ☐
Yes No
Ja Nein

(Number) (Country)
(Nummer) (Land)
(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☐ ☐
Yes No
Ja Nein

(Number) (Country)
(Nummer) (Land)
(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☐ ☐
Yes No
Ja Nein

Ich beanspruche hiermit gemäss Absatz 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 120, den Vorzug aller unten aufgeführten Anmeldungen und falls der Gegenstand aus jedem Anspruch dieser Anmeldung nicht in einer früheren amerikanischen Patentanmeldung laut dem ersten Paragraphen des Absatzes 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 122 offenbart ist, erkenne ich gemäss Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) meine Pflicht zur Offenbarung von Informationen an, die zwischen dem Anmeldedatum der früheren Anmeldung und dem nationalen oder PCT internationalen Anmeldedatum dieser Anmeldung bekannt geworden sind.

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §122 I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Serial No.)
(Anmeldeseriennummer)
(Filing Date)
(Anmeldedatum)

(Status)
(patentiert, anhängig,
aufgegeben)
(Status)
(patented, pending,
abandoned)

(Application Serial No.)
(Anmeldeseriennummer)
(Filing Date)
(Anmeldedatum)

(Status)
(patentiert, anhängig,
aufgegeben)
(Status)
(patented, pending,
abandoned)

Ich erkläre hiermit, dass alle von mir in der vorliegenden Erklärung gemachten Angaben nach meinem besten Wissen und Gewissen der vollen Wahrheit entsprechen, und dass ich diese eidesstattliche Erklärung in Kenntnis dessen abgebe, dass wissentlich und vorsätzlich falsche Angaben gemäss Paragraph 1001, Absatz 18 der Zivilprozessordnung der Vereinigten Staaten von Amerika mit Geldstrafe belegt und/oder Gefängnis bestraft werden koennen, und dass derartig wissentlich und vorsätzlich falsche Angaben die Gültigkeit der vorliegenden Patentanmeldung oder eines darauf erteilten Patentes gefährden können.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: (Name und Registrationsnummer anführen)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

And I hereby appoint Messrs. John D. Simpson (Registration No. 19,842), Dennis A. Gross (24,410), Robert M. Barrett, (30,142), Steven H. Noll (28,982), Kevin W. Guynn (29,927), Robert M. Ward (26,517), Brett A. Valiquet (27,841), Edward A. Lehman (22,312), David R. Metzger (32,919), James D. Hobart (24,149), Melvin A. Robinson (31,870), Joseph P. Reagan (35,332), Michael R. Hull (35,902), Michael S. Leonard (37,557), William E. Vaughan (39,056) and Lewis T. Steadman (17,074), all members of the firm of Hill & Simpson, A Professional Corporation

Telefongespräche bitte richten an:
(Name und Telefonnummer)

Direct Telephone Calls to: (name and telephone number)

312/876-0200
Ext. 3261

Postanschrift:

Send Correspondence to:

HILL & SIMPSON
A Professional Corporation
85th Floor Sears Tower, Chicago, Illinois 60606

Voller Name des einzigen oder ursprünglichen Erfinders: <u>Jürgen Kockmann</u>	Full name of sole or first inventor:
Unterschrift des Erfinders <u>X: Jürgen Kockmann</u>	Inventor's signature <u>X: 8.5.00</u>
Wohnsitz <u>Gronau, Germany Düsseldorf</u>	Residence
Staatsangehörigkeit <u>German</u>	Citizenship <u>DEX</u>
Postanschrift <u>52 Oststrasse 52</u>	Post Office Address <u>Albrecht-Dürer-Str. 16</u>
<u>D-48599 Gronau</u> Bundesrepublik Deutschland	

(Bitte entsprechende Informationen und Unterschriften im Falle von weiteren Miterfindern angeben).

(Supply similar information and signature for subsequent joint inventors).

Voller Name des zweiten Miterfinders (falls zutreffend): <u>Uwe Sydon</u>		Full name of second joint inventor, if any:	
Unterschrift des Erfinders <u>Uwe Sydon</u>	Datum <u>12.05.00</u>	Inventor's signature	Date
Wohnsitz <u>Düsseldorf, Germany</u> <u>DEX</u>		Residence	
Staatsangehörigkeit <u>German</u>		Citizenship	
Postanschrift <u>Rosspfad 7</u> <u>Amsterdamerstrasse 32</u>		Post Office Address	
<u>D-404⁸⁹</u> <u>Düsseldorf</u> <u>Bundesrepublik Deutschland</u>			
Voller Name des dritten Miterfinders (falls zutreffend): <u>Hermann-Josef Terglane</u>		Full name of third joint inventor, if any:	
Unterschrift des Erfinders <u>Hermann-Josef Terglane</u>	Datum <u>16. Mai 2000</u>	Inventor's signature	Date
Wohnsitz <u>Heek, Germany</u> <u>DEX</u>		Residence	
Staatsangehörigkeit <u>German</u>		Citizenship	
Postanschrift <u>Nelkenweg 20</u>		Post Office Address	
<u>D-48619 Heek</u> <u>Bundesrepublik Deutschland</u>			
Voller Name des vierten Miterfinders (falls zutreffend):		Full name of fourth joint inventor, if any:	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	

(Bitte entsprechende Informationen und Unterschriften im Falle von zweiten und weiteren Miterfindern angeben).

(Supply similar information and signature for second and subsequent joint inventors).